# Rapid Screening for DEHP in Food and Beverage Products

### GOAL

To successfully screen for the presence of di(2-ethylhexyl) phthalate (DEHP) in food and beverage products using a simple, rapid technique with minimal sample preparation and no chromatographic separation.

## BACKGROUND

Di(2-ethylhexyl) phthalate (DEHP) is a costeffective general purpose plasticizer used mainly for making plastics soft and pliable in building materials such as flooring, cables, as well as medical devices.

In May 2011, the Taiwan Food and Drug Administration (TFDA) found DEHP in powdered probiotics, which was then traced back to the clouding agent supplier. The so-called "clouding agent" is a legal food additive that is commonly used in beverage, food, and dietary supplements. However, the supplier intentionally replaced the additives with DEHP in order to cut costs. DEHP is 20 times more toxic than melamine, and is classified as a class B2, probable human carcinogen, under the U.S. Environmental Protection Agency. Consumption of plasticizer-tainted food or beverage products increases the risk of reproductive abnormalities. Screen for DEHP in less than 2 minutes with minimal sample preparation and no chromatographic separation.




Figure 1. TIC traces of DEHP spiked at 1 mg/kg (blue) versus blank (red) in flavored syrup (A), fruit juice (B), fruit jam (C), and health supplement tablet (D).

THE SCIENCE OF

The regulations of Food Containers and Appliances (Taiwan) mandate that the maximum level of DEHP dissolved from plastic items must not exceed 1.5 ppm, and that no DEHP can be added to food products. The international acceptance criteria of daily maximum consumption ranges from 1.2 to 8.4 mg for a 60 kg adult.

Food safety regulators require that all products found to be contaminated with DEHP be recalled and removed from the shelves immediately. Rigorous tests must be carried out on six categories of food and beverages including sports drinks, fruit juices, tea drinks, fruit jam and jellies, food powders, and health supplement tablets. This poses a major analytical challenge, as the complexity of food matrices requires the use of different extraction techniques. Thus the ability to rapidly screen for the presence of DEHP using a simple technique with minimal sample preparation and no chromatographic separation would be advantageous.



The Atmospheric Solids Analysis Probe (ASAP).

## THE SOLUTION

The Waters® Atmospheric Solids Analysis Probe (ASAP), together with the Xevo® TQ MS System, is able to rapidly screen for the presence of DEHP in less than two minutes. Minimal sample preparation and no chromatographic separation are required for this analysis. This method is able to detect for DEHP confidently in a range of food matrices.

The glass capillary was dipped into the food sample and any excess sample was wiped off. The capillary was then attached onto the ASAP probe and loaded directly into the source enclosure of the Xevo TQ MS System. The desolvation gas was rapidly heated to 450 °C within 20 seconds and acquired using multiple reaction monitoring (MRM) with three transitions listed in Table 1.

Precursor ion	Product ion	Cone voltage (V)	Collision energy (eV)
391.3	149	19	20
	167		14
	279		9

Table 1. MRM transitions for DEHP analysis.

### SUMMARY

DEHP was successfully detected at 1 ppm in a range of food matrices. Requiring minimal sample preparation and with no chromatographic separation, this was achieved in less than 2 minutes per sample using ASAP and Xevo TQ MS.

This solution provides an increase in lab productivity and efficiency due to the ease of sample preparation (direct sampling from the matrix) and shorter analysis times. At the same time, with the minimal use of solvent in this analysis, the cost of lab consumables is also minimized.



Waters and Xevo are registered trademarks of Waters Corporation. The Science of What's Possible is a trademark of Waters Corporation. All other trademarks are the property of their respective owners.

©2011 Waters Corporation. Produced in the U.S.A. June 2011 720004015EN LL-PDF

Waters Corporation

34 Maple Street Milford, MA 01757 U.S.A. T: 1 508 478 2000 F: 1 508 872 1990 www.waters.com

