CLICK ON THE UNDERLINED BLUE TEXT FOR DETAILS ON THE PRODUCTS USED IN THIS APPLICATION

TEST CONDITIONS

Chromatographic Conditions

ACQUITY UPLC® BEH Amide Column:

2.1 x 100 mm, 1.7 µm

Part Number: 186004801

Mobile Phase A: 80/20 MeCN/H₂O with 0.2%

triethylamine [TEA]

30/70 MeCN/H₂O with 0.2% Mobile Phase B:

triethylamine [TEA]

Flow Rate: 0.13 mL/min

Flow Profile: 90% A/10% B (75% MeCN with

0.2% TEA)

Injection Volume: 1.3 μL (PLNO)

Sample Concentration: Standards at 1 mg/mL each

Sample Diluent: 50/50 MeCN/H₂0


35°C Column Temperature:

Strong Needle Wash: 20/80 MeCN/H₂O (800 μL) Weak Needle Wash: $75/25 \text{ MeCN/H}_{2} O (500 \mu L)$


Seal Wash: 50/50 MeCN/H₂0

Waters ACQUITY UPLC with ELSD Instrument:

STRUCTURES




Sucrose **Fructose**



Lactose

p-Toluamide (unretained compound)



Glucose

ELSD Conditions

200 Gain: Pressure: 40 psi 40 °C **Drift Tube Temperature:** Nebulizer: Cooling Data Rate: 10 pps Filter Time Constant:

COMPOUNDS

1. p-Toluamide 4. Sucrose 5. Maltose

